

KATUN[®]
SUCCESS MADE SIMPLE.



PRODUCT SPECIFICATIONS

**Arivia M2125/
M2130/M3135**

A3 MONOCHROME MULTIFUNCTION PRINTER

PRODUCT SPECIFICATIONS | Arivia M2125/M2130/M3125

BASIC SPECIFICATIONS/COPY FUNCTION

	Arivia M2125	Arivia M2130	Arivia M3125	
Type	Desktop / Console			
Memory capacity	4 GB (Max: 4 GB)			
Storage Device Capacity*1	128 GB			
Scan Resolution	600 x 600 dpi			
Printing Resolution	1200 x 1200 dpi			
Halftone/Printable Colors	256 levels of gray			
Warm-up Time*2	31 seconds or less (23 degrees Celsius room temperature)			
Recovery Time (Recovery Time from Sleep mode)	15 seconds or less [AC 120 V model] 14 seconds or less [AC 220 V model] (23 degrees Celsius room temperature)			
Original Size	Maximum of A3, 11 x 17", 297 x 432 mm for both Sheet and Book			
Paper Size	Max	A3, 11 x 17"		
	Min	A5 [Postcard (100 x 148 mm), when using Bypass Tray]		
	Image loss width	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm		
Paper Weight*3	Paper Tray	60 to 256 gsm / 16 lb. bond to 142 lb. index		
	Bypass Tray	60 to 216 gsm / 16 lb. bond to 57 lb. bond		
First Copy Output Time	4.5 sec. (A4 LEF/Letter LEF)			
Reduce / Enlarge	Size-to-Size	1:1 +/- 0.7 %		
	Preset	Preset[AC 220V Model]: 50 %, 70 %, 81 %, 94 %, 122 %, 127 %, 141 %, 200 %[AC 120V Model]: 50 %, 70 %, 78 %, 94 %, 129 %, 141 %, 180 %, 200 %		
	Variable	25 to 400 % (in 1 % increments)		
Continuous Copy Speed*4	A4 LEF / JIS B5 LEF Letter LEF	35 ppm	30 ppm	25 ppm
	A4 / JIS B5	26 ppm	23 ppm	19 ppm
	JIS B4	13 ppm	13 ppm	11 ppm
	Legal	22 ppm	20 ppm	16 ppm
	A3	19 ppm	17 ppm	14 ppm
Paper Tray Capacity*5	Standard	520 sheets x 1-tray + Bypass Tray 100 sheets		
	Optional	1 Tray Module: 520 sheets x 1-tray 1 Tray Module with Cabinet: 520 sheets x 1-tray 3 Tray Module: 520 sheets x 3-tray Tandem Tray Module: 520 sheets x 1-tray + 870 sheets x 1-Tray + 1180 sheets x 1-Tray High Capacity Feeder B1: 2000 sheets x 1 Tray		
	Max	2180 sheets [Standard + 3 Tray Module] 3190 sheets [Standard + Tandem Tray Module] 5190 sheets [Standard + Tandem Tray Module + High Capacity Feeder B1]		
Continuous Copy *6	999 sheets			
Output Tray Capacity*7	Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF)			
Power Supply	AC 110 - 127 V ±10%, 12 A, 50/60 ±3% Hz common AC 220 - 240 V ±10%, 8A, 50/60 ±3% Hz common			
Maximum Power Consumption	1.45 kW or less (AC110 V ±10%) 1.67 kW or less (AC127 V ±10%) 1.76 kW or less (AC220 V ±10%) 1.92 kW or less (AC240 V ±10%)			
Dimensions	Sleep Mode: 0.3 W or less, Ready Mode: 96 W or less (AC 120V model) Sleep Mode: 0.4 or less, Ready Mode: 94 W or less (AC 220V model)			
	W 590 x D 659 x H 768 mm / W 23.3 x D 26.0 x H 30.3" W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 1 Tray Module with Cabinet Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 3 Tray Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional Tandem Tray Module is installed.)			
	57 kg / 126lb. 79 kg / 175lb. (When optional 1 Tray Module with Cabinet is installed.) 82 kg / 181lb. (When optional 3 Tray Module is installed.) 87 kg / 192lb. (When optional Tandem Tray Module is installed.)			
Weight*8	57 kg / 126lb. 79 kg / 175lb. (When optional 1 Tray Module with Cabinet is installed.) 82 kg / 181lb. (When optional 3 Tray Module is installed.) 87 kg / 192lb. (When optional Tandem Tray Module is installed.)			
Space Requirement	W 971 x D 659 mm / W38.3 x 26.0" (when the Bypass Tray is fully extended)			

*1: The Storage Device Capacity is not totally available for customers.

*2: It may change depending on usage conditions.

*3: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement.

*4 The speed may be reduced due to the image quality adjustment.

*5: 20 lb./75 gsm paper.

*6: Copy process may stop temporarily for stabilization of image quality.

*7: 70 gsm paper.

*8: Including Toner Cartridge.

PRINT FUNCTION

Type	Built-in type		
Continuous Print Speed*3	Same as the Basic Specifications / Copy Function		
Printing Resolution	Standard	[PCL Driver] Standard: 600 x 600 dpi, High Resolution: 1200 x 1200 dpi	
	Standard	[Adobe® PostScript® 3TM Driver] Standard: 600 x 600 dpi, High Resolution: 1200 x 1200 dpi	
Page Description Language	Standard	PCL5 / PCL6	
	Standard	Adobe® PostScript® 3TM	
Network Protocol	Ethernet (Standard)	TCP/IP (Ipd, IPP, Port9100, WSD)	
	Standard	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)	
Supported Operating System*4	Standard	[Mac OS X Driver] MacOS 14 / 13 / 12 / 11	
	Standard	[Adobe® PostScript® 3TM Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 / 13 / 12 / 11	
Fonts	Standard	PCL : 85 fonts	
	Standard	Adobe® PostScript® 3TM Kit:136 European fonts	
Emulation	Standard	PDF, XPS, TIFF, JPEG, Adobe® PostScript® 3TM, PCL5 / PCL6, HP-GL2	
	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0	
Interface	Standard	Wireless LAN (IEEE 802.11 a / b / g / n / ac)	
	Optional	Wireless LAN (IEEE 802.11 a / b / g / n / ac)	

Note: WSD stands for Web Services on Devices.

Note: XPS stands for XML Paper Specification.

*1: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document.

*2: Please refer to our official website for the latest supported OS.

SCAN FUNCTION

Type	Color Scanner		
Original Size	Same as the Basic Specifications / Copy Function		
Scan Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi		
Scan Speed	Same as the Scan Speed for the Duplex Automatic Document Feeder		
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T	
	Optional	Wireless LAN (IEEE 802.11 a / b / g / n / ac)	
Scan to Folder	Network Protocol	TCP/IP (WebDAV, HTTP)	
	File Format	Monochrome binary: TIFF, PDF*1 Grayscale: TIFF, JPEG*2, PDF*1 Full Color: TIFF, JPEG, PDF*1, Highly compressed PDF*1	
	Driver	TWAIN Interface support	
Scan to PC	Operating System*3	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)	
	Network Protocol	TCP/IP (SMB, FTP, SFTP)	
Scan to e-mail	Operating System	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14*4 / 13*4 / 12*4 / 11*4	
	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF	
Scan to e-mail	Network Protocol	TCP/IP (SMTP)	
	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF	

*1: When Internet Services is used.

*2: When Network Scanner Utility 3 is used.

*3: Please refer our official website for the latest supported OS.

*4: Only SMB is supported.

FAX FUNCTION (OPTIONAL)

Original Size	Max: A3, 11 x 17", Long document (Longest 600 mm / 23.7")
Recording Paper Size	Max: A3, 11 x 17"; Min: A5
Transmission Time	2 seconds and more but fewer than 3 seconds*
Transmission Mode	ITU-T G3
	Standard 8 x 3.85 line/mm, 200 x 100 dpi
	Fine 8 x 7.7 line/mm, 200 x 200 dpi
Scanning Resolution	Super Fine (400dpi) 16 x 15.4 line/mm, 400 x 400 dpi
	Super Fine (600dpi) 600 x 600 dpi
Coding Method	MH, MR, MMR, JBIG
Transmission Speed	G3: 33.6 / 31.2 / 28.8 / 26.4 / 24.0 / 21.6 / 19.2 / 16.8 / 14.4 / 12.0 / 9.6 / 7.2 / 4.8 / 2.4 kbps
Applicable Lines	Telephone subscriber line, PBX, Fax communication (PSTN)

* When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

DIRECT FAX FUNCTION (OPTIONAL)

Original Size	A3, JIS B4, A4
Resolution	As same image quality indicated in Scanning Resolution for Fax Function
Transmission Speed	Same as the Fax Function
Applicable Lines	Same as the Fax Function
Supported Operating System*	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) [Mac OS X Driver] MacOS 14 / 13 / 12 / 11

*: Please refer to our official website for the latest supported OS.

INTERNET FAX FUNCTION (OPTIONAL)

Original Size	A3, JIS B4, A4
Scanning Resolution	Same as the Fax Function
File Format	Format: TIFF-FB; Compression method: MH, MMR, JBIG
Profile	TIFF-S, TIFF-F, TIFF-J
Network Protocol	Transmission SMTP Reception SMTP, POP3
Interface	Standard Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T

DUPLEX FUNCTION

Paper Size	Same as the Basic Specifications / Copy Function
Paper Weight	60 to 169 gsm / 16 lb. bond to 45 lb. bond

DUPLEX AUTOMATIC DOCUMENT FEEDER C2-PC [1 PASS, 2 SIDED SCANNING]

Type	1 pass, 2 sided scanning Duplex Automatic Document Feeder
Original Size / Paper Weight	Max: A3, 11 x 17"; Min: A6*1 38 to 128 gsm / 11 lb. bond to 34 lb. bond (In Duplex: 50 to 128 gsm / 14 lb. bond to 34 lb. bond)
Capacity *2	130 sheets
Scan Speed *3	Copy (A4 LEF, Simplex) M2125: B/W: 25 ipm, Color: 25 ipm M2130: B/W: 30 ipm, Color: 30 ipm M3135: B/W: 35 ipm, Color: 35 ipm Scan B/W: 80 ipm, Color: 80 ipm (1 pass, 2 sided scanning: B/W 80 ipm, Color 80 ipm) [Standard Document (A4 LEF/Letter LEF), 200 dpi, to Folder.]

*1: The minimum custom size is 49x85 mm / 2.0 x 3.4".

*2: Custom sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm.

*3: 70 gsm paper.

*4: The scanning speed varies depending on the documents.

HIGH CAPACITY FEEDER B1 (OPTIONAL)

Paper Size	A4 LEF, Letter LEF, JIS B5 LEF
Paper Weight	55 to 216 gsm / 15 lb. bond to 57 lb. bond
Feeding Capacity / Number of Tray *1	2000 sheets x 1-tray
Dimensions	W 389 x D 610 x H 377 mm / W 15.4 x D 24.1 x H 14.9"
Weight	29 kg / 64 lb.
Space Requirement *2	W 1056 x D 720 mm / W 41.6 x D 28.4"

*1: 80 gsm paper.

*2: Main Unit + High Capacity Feeder B1; When the Bypass Tray are fully extended.

Finisher-A2(Optional)

Type	Sort (Offset available) / Stack (Offset available) Default: No Offset
Paper Size	Max: A3, 11 x 17"; Min: Postcard (100 x 148 mm)
Paper Weight	60 to 256 gsm / 16 lb. bond to 142 lb. index
Paper Capacity *1	[Without Stapling] A4: 500 sheets; JIS B4: 250 sheets; A3 or larger: 200 sheets; Mixed Size Stacking*2: 250 sheets [With Stapling] 30 sets
Staple	Capacity gsm or less) A4: 50 sheets (90 gsm or less), JIS B4 or larger: 30 sheets (90 gsm or less) Paper Size Max: A3, 11 x 17"; Min: JIS B5 LEF Paper Weight 60 to 256 gsm / 16 lb. bond to 142 lb. index Position Single stapling, Dual stapling
Dimensions	W 658 x D 461 x H 238 mm / W 25.9 x D 18.2 x H 9.4" 11 kg / 25lb
Space Requirement (When connected to the main unit) *2	W 1132 x D 659 mm / W 44.6 x D 26.0"

*1: 70 gsm paper.

*2: When larger size sheets are stacked on top of smaller size sheets.

*3: Width 478 mm when the paper support is stored.

*4: Main Unit + Finisher-A2; when the paper support is pulled out and the Bypass Tray is fully extended.

FINISHER-B4 (OPTIONAL)

Type	Sort (Offset available ^{*1*}) / Stack (Offset available ^{*1*})
Paper Size^{*3}	Max: A3, 11 x 17"; Min: A5
Paper Weight^{*4}	60 to 256 gsm / 16 lb. bond to 142 lb. index
Paper Capacity^{*5}	[Without Stapling] A4: 2000 sheets, JIS B4 or larger: 1000 sheets, Mixed Size Stacking ^{*6} : 300 sheets [With Stapling] A4: 100 sets or 1000 sheets ^{*7} , JIS B4 or larger: 75 sets or 750 sheets [With Booklet Finishing ^{*8}] 50 sets or 600 sheets [With Fold ^{*9}] 500 sheets
Capacity	50 sheets (90 gsm or less)
Paper Size^{*10}	Max: A3, 11 x 17"; Min: A5 LEF
Staple Paper Weight	60 to 256 gsm / 16 lb. bond to 142 lb. index
Position	Single stapling, Dual stapling
Number of Holes	2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications)
Punch^{*11} Paper Size^{*12}	Max: A3, 11 x 17"; Min: A5 LEF
Punch Paper Weight	60 to 220 gsm / 16 lb. bond to 122 lb. index
Capacity	Saddle Staple: 15 sheets; Single Fold: 5 sheets
Booklet Finishing^{*8} Paper Size	Max: A3, 11 x 17"; Min: A4, Letter
Booklet Finishing Paper Weight	Saddle Staple: 60 to 80 gsm / 16 lb. bond to 21 lb. bond ^{*13} Single Fold: 60 to 105 gsm / 18 lb. bond to 28 lb. bond
Dimensions^{*14}	W 607 x D 653 x H 1041 mm / W 23.9 x D 25.7 x H 41.0" With Booklet Finisher: W 607 x D 673 x H 1079 mm / W 23.9 x D 26.5 x H 42.5"
Weight ^{*15}	26 kg / 58 lb. Punch Kit: + 2 kg / 5 lb. Booklet Maker Unit: + 10 kg / 22 lb.
Space Requirement (When connected to the main unit) ^{*16}	W 1519 x D 659 mm / W 59.8 x D 26.0" With Booklet Finisher: W 1519 x D 673 mm / W 59.8 x D 26.5"

Installation Kit Required.

Note: Finisher-B4 is available only when optional 1 Tray Module or 3 Tray Module or Tandem Tray Module is attached to Main Unit.

*1: The offset feature is set to disabled by factory default. The setting can be changed as necessary.

*2: Outputs less than 210 mm width are delivered without offset stacking.

*3: Paper in the sizes larger than A3 or 11 x 17" or smaller than A5 are delivered to the Centre Tray.

*4: 70 gsm paper.

*5: When larger size sheets are stacked on top of smaller size sheets.

*6: 75 sets or 750 sheets with dual stapling.

*7: The Booklet Finishing function requires the optional Booklet Maker Unit for Finisher-B. Make a crease allows you to fold easily. After a job with the Booklet Finishing function specified has been output, the next job may not be delivered until the sheets are removed from the output tray. Also, if larger size sheets are stacked on top of smaller size sheets after a job with the Booklet Finishing function specified has been run, the next job may not be delivered until the sheets are removed from the output tray.

*8: Available staple positions vary depending on the paper size.

*9: The Punch function requires the optional 2/4 Hole Punch Kit for Finisher-B or US 2/3 Hole Punch Kit for Finisher-B.

*10: Available number of punch holes varies depending on the paper size.

*11: Covers can be up to 220 gsm (Extra Heavyweight).

*12: Inner connector within the body is excluded.

*13: Main Unit + Finisher-B4; When the paper support is pulled out and the Bypass Tray is fully extended.

Arivia M2125/M2130/M3135

MONOCHROME A3 MULTIFUNCTION PRINTER

Katun's portfolio of Arivia MFP's for large workgroups feature state-of-the-art technology that makes it easy to run your business and maximize productivity. Designed to integrate into any office environment, Arivia MFP's are designed to withstand today's security threats, offer an intuitive user experience, and deliver enhanced workflow solutions. Smartly designed for reliability and to minimize service calls, and with print speeds up to 65ppm, scan speeds up to 270ppm and a full range of input and finishing options, Arivia is powerful asset to your business.



CONSUMABLE YIELDS

	Arivia M2125	Arivia M2130	Arivia M3135
Toner Yield*	30,000	30,000	30,000
Starter Toner Yield*	10,800	10,800	10,800
Drum Yield	70,400	82,700	95,300
Waste Toner Cartridge Yield	N/A	N/A	N/A

* Based on 5% page coverage.

For complete information on Katun products, please visit: www.katun.com

© 2024 Katun. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KATUN®

7760 France Ave. So. Suite 340
Minneapolis, MN 55435
1-800-328-2965 | katun.com

