

**KATUN**<sup>®</sup>  
SUCCESS MADE SIMPLE.



PRODUCT SPECIFICATIONS

Arivia M2125,  
M2130, M3135

A3 MONOCHROME MULTIFUNCTION PRINTER

# PRODUCT SPECIFICATIONS | Arivia M2125, M2130, M3135

## BASIC SPECIFICATIONS/COPY FUNCTION

	Arivia M3135	Arivia M2130	Arivia M2125	
<b>Type</b>	Desktop / Console			
<b>Memory capacity</b>	4 GB (Max: 4 GB)			
<b>Storage Device Capacity<sup>*1</sup></b>	128 GB			
<b>Scan Resolution</b>	600 x 600 dpi			
<b>Printing Resolution</b>	1200 x 1200 dpi			
<b>Halftone/Printable Colors</b>	256 levels of gray			
<b>Warm-up Time<sup>*2</sup></b>	31 seconds or less (23 degrees Celsius room temperature)			
<b>Recovery Time (Recovery Time from Sleep mode)</b>	15 seconds or less [AC 120 V model] 14 seconds or less [AC 220 V model] (23 degrees Celsius room temperature)			
<b>Original Size</b>	Maximum of A3, 11 x 17", 297 x 432 mm for both Sheet and Book			
<b>Paper Size</b>	<b>Max</b>	A3, 11 x 17"		
	<b>Min</b>	A5 [Postcard (100 x 148 mm), when using Bypass Tray]		
	<b>Image loss width</b>	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm		
<b>Paper Weight<sup>*3</sup></b>	<b>Paper Tray</b>	60 to 256 gsm / 16 lb. bond to 142 lb. index		
	<b>Bypass Tray</b>	60 to 216 gsm / 16 lb. bond to 57 lb. bond		
<b>First Copy Output Time</b>	4.5 sec. (A4 LEF/Letter LEF)			
<b>Reduce / Enlarge</b>	<b>Size-to-Size</b>	1: 1 +/- 0.7 %		
	<b>Preset</b>	Preset[AC 220V Model]: 50 %, 70 %, 81 %, 94 %, 122 %, 127 %, 141 %, 200 % [AC 120V Model]: 50 %, 70 %, 78 %, 94 %, 129 %, 141 %, 180 %, 200 %		
	<b>Variable</b>	25 to 400 % (in 1 % increments)		
<b>Continuous Copy Speed<sup>*4</sup></b>	<b>A4 / JIS B5 Letter LEF</b>	35 ppm	30 ppm	25 ppm
	<b>A4 / JIS B5</b>	26 ppm	23 ppm	19 ppm
	<b>JIS B4</b>	13 ppm	13 ppm	11 ppm
	<b>Legal</b>	22 ppm	20 ppm	16 ppm
	<b>A3</b>	19 ppm	17 ppm	14 ppm
<b>Paper Tray Capacity<sup>*5</sup></b>	<b>Standard</b>	520 sheets x 1-tray + Bypass Tray 100 sheets 1 Tray Module: 520 sheets x 1-tray 1 Tray Module with Cabinet: 520 sheets x 1-tray 3 Tray Module: 520 sheets x 3-tray Tandem Tray Module: 520 sheets x 1-tray + 870 sheets x 1-tray + 1180 sheets x 1-tray High Capacity Feeder B1: 2000 sheets x 1 Tray		
	<b>Optional</b>	2180 sheets [Standard + 3 Tray Module] 3190 sheets [Standard + Tandem Tray Module] 5190 sheets [Standard + Tandem Tray Module + High Capacity Feeder B1]		
	<b>Max</b>			
<b>Continuous Copy <sup>*6</sup></b>	999 sheets			
<b>Maximum Duty Cycle</b>	150K per month	120K per month	100K per month	
<b>Output Tray Capacity<sup>*7</sup></b>	Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF)			
<b>Power Supply</b>	AC 110 - 127 V ±10%, 12 A, 50/60 ±3% Hz common AC 220 - 240 V ±10%, 8A, 50/60 ±3% Hz common			
<b>Maximum Power Consumption</b>	1.45 kW or less (AC110 V ±10%) 1.67 kW or less (AC127 V ±10%) 1.76 kW or less (AC220 V ±10%) 1.92 kW or less (AC240 V ±10%)			
	Sleep Mode: 0.3 W or less, Ready Mode: 96 W or less (AC 120V model) Sleep Mode: 0.4 or less, Ready Mode: 94 W or less (AC 220V model)			
<b>Dimensions</b>	W 590 x D 659 x H 768 mm / W 23.3 x D 26.0 x H 30.3" W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 1 Tray Module with Cabinet Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 3 Tray Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional Tandem Tray Module is installed.)			
<b>Weight<sup>*8</sup></b>	57 kg / 126lb. 79 kg / 175lb. (When optional 1 Tray Module with Cabinet is installed.) 82 kg / 181lb. (When optional 3 Tray Module is installed.) 87 kg / 192lb. (When optional Tandem Tray Module is installed.)			
<b>Space Requirement</b>	W 971 x D 659 mm / W38.3 x 26.0" (when the Bypass Tray is fully extended)			

\*1: The Storage Device Capacity is not totally available for customers.

\*2: It may change depending on usage conditions.

\*3: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement.

\*4 The speed may be reduced due to the image quality adjustment.

\*5: 20 lb./75 gsm paper.

\*6: Copy process may stop temporarily for stabilization of image quality.

\*7: 70 gsm paper.

\*8: Including Toner Cartridge.

## PRINT FUNCTION

<b>Type</b>	Built-in type	
<b>Continuous Print Speed<sup>*3</sup></b>	Same as the Basic Specifications / Copy Function	
<b>Printing Resolution</b>	<b>Standard</b>	[PCL Driver] Standard: 600 x 600 dpi, High Resolution: 1200 x 1200 dpi
		[Adobe® PostScript® 3TM Driver] Standard: 600 x 600 dpi, High Resolution: 1200 x 1200 dpi
<b>Page Description Language</b>	<b>Standard</b>	PCL5 / PCL6
		Adobe® PostScript® 3TM
<b>Network Protocol</b>	<b>Ethernet (Standard)</b>	TCP/IP (Ipd, IPP, Port9100, WSD)
<b>Supported Operating System<sup>*4</sup></b>	<b>Standard</b>	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)
		[Mac OS X Driver] MacOS 14 / 13 / 12 / 11
<b>Fonts</b>	<b>Standard</b>	[Adobe® PostScript® 3TM Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 / 13 / 12 / 11
		PCL : 85 fonts Adobe® PostScript® 3TM Kit:136 European fonts
<b>Emulation</b>	<b>Standard</b>	PDF, XPS, TIFF, JPEG, Adobe® PostScript® 3TM, PCL5 / PCL6, HP-GL2
<b>Interface</b>	<b>Standard</b>	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0
	<b>Optional</b>	Wireless LAN (IEEE 802.11 a / b / g / n / ac)
<b>Wireless Printing</b>	<b>Standard</b>	Airprint, Mopria® Print Services
	<b>Optional</b>	WiFi Direct

Note: WSD stands for Web Services on Devices.

Note: XPS stands for XML Paper Specification.

\*1: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document.

\*2: Please refer to our official website for the latest supported OS.

## SCAN FUNCTION

<b>Type</b>	Color Scanner	
<b>Original Size</b>	Same as the Basic Specifications / Copy Function	
<b>Scan Resolution</b>	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi	
<b>Scan Speed</b>	Same as the Scan Speed for the Duplex Automatic Document Feeder	
<b>Interface</b>	<b>Standard</b>	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T
	<b>Optional</b>	Wireless LAN (IEEE 802.11 a / b / g / n / ac)
<b>Scan to Folder</b>	<b>Network Protocol</b>	TCP/IP (WebDAV, HTTP)
	<b>File Format</b>	Monochrome binary: TIFF, PDF <sup>*1</sup> , Searchable PDF and PDF/A <sup>*1</sup> Grayscale: TIFF, JPEG <sup>*2</sup> , PDF <sup>*1</sup> , Searchable PDF and PDF/A <sup>*1</sup> Full Color: TIFF, JPEG, PDF <sup>*1</sup> , Highly compressed PDF <sup>*1</sup> , Searchable PDF and PDF/A <sup>*1</sup>
<b>Scan to PC</b>	<b>Driver</b>	TWAIN Interface support
	<b>Operating System<sup>*3</sup></b>	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)
<b>Scan to e-mail</b>	<b>Network Protocol</b>	TCP/IP (SMB, FTP, SFTP)
	<b>Operating System</b>	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 <sup>*4</sup> / 13 <sup>*4</sup> / 12 <sup>*4</sup> / 11 <sup>*4</sup>
<b>Wireless Scanning</b>	<b>File Format</b>	Monochrome binary: TIFF, PDF, Searchable PDF and PDF/A <sup>*1</sup> Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF, Searchable PDF and PDF/A <sup>*1</sup>
	<b>Network Protocol</b>	TCP/IP (SMTP)
<b>Wireless Scanning</b>	<b>File Format</b>	Monochrome binary: TIFF, PDF, Searchable PDF and PDF/A <sup>*1</sup> Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF, Searchable PDF and PDF/A <sup>*1</sup>
	<b>File Format</b>	Monochrome binary: TIFF, PDF, Searchable PDF and PDF/A <sup>*1</sup> Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF, Searchable PDF and PDF/A <sup>*1</sup>

\*1: When Internet Services is used.

\*2: When Network Scanner Utility 3 is used.

\*3: Please refer our official website for the latest supported OS.

\*4: Only SMB is supported.

### FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	Max: A3, 11 x 17", Long document (Longest 600 mm / 23.7")
<b>Recording Paper Size</b>	Max: A3, 11 x 17"; Min: A5
<b>Transmission Time</b>	2 seconds and more but fewer than 3 seconds*
<b>Transmission Mode</b>	ITU-T G3
	<b>Standard</b> 8 x 3.85 line/mm, 200 x 100 dpi
	<b>Fine</b> 8 x 7.7 line/mm, 200 x 200 dpi
<b>Scanning Resolution</b>	<b>Super Fine (400dpi)</b> 16 x 15.4 line/mm, 400 x 400 dpi
	<b>Super Fine (600dpi)</b> 600 x 600 dpi
<b>Coding Method</b>	MH, MR, MMR, JBIG
<b>Transmission Speed</b>	G3: 33.6 / 31.2 / 28.8 / 26.4 / 24.0 / 21.6 / 19.2 / 16.8 / 14.4 / 12.0 / 9.6 / 7.2 / 4.8 / 2.4 kbps
<b>Applicable Lines</b>	Telephone subscriber line, PBX, Fax communication (PSTN)

\* When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

### DIRECT FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	A3, JIS B4, A4
<b>Resolution</b>	As same image quality indicated in Scanning Resolution for Fax Function
<b>Transmission Speed</b>	Same as the Fax Function
<b>Applicable Lines</b>	Same as the Fax Function
<b>Supported Operating System*</b>	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) [Mac OS X Driver] MacOS 14 / 13 / 12 / 11

\*: Please refer to our official website for the latest supported OS.

### INTERNET FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	A3, JIS B4, A4
<b>Scanning Resolution</b>	Same as the Fax Function
<b>File Format</b>	Format: TIFF-FB; Compression method: MH, MMR, JBIG
<b>Profile</b>	TIFF-S, TIFF-F, TIFF-J
<b>Network Protocol</b>	<b>Transmission Reception</b> SMTP, POP3
<b>Interface Standard</b>	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T

### DUPLEX FUNCTION

<b>Paper Size</b>	Same as the Basic Specifications / Copy Function
<b>Paper Weight</b>	60 to 169 gsm / 16 lb. bond to 45 lb. bond

### DUPLEX AUTOMATIC DOCUMENT FEEDER C2-PC [1 PASS, 2 SIDED SCANNING]

<b>Type</b>	1 pass, 2 sided scanning Duplex Automatic Document Feeder
<b>Original Size / Paper Weight</b>	Max: A3, 11 x 17"; Min: A6*1 38 to 128 gsm / 11 lb. bond to 34 lb. bond (In Duplex: 50 to 128 gsm / 14 lb. bond to 34 lb. bond)
<b>Capacity*2</b>	130 sheets
<b>Scan Speed*3</b>	<b>Copy (A4 LEF, Simplex)</b> M2125: B/W: 25 ppm, Color: 25 ppm M2130: B/W: 30 ppm, Color: 30 ppm M3135: B/W: 35 ppm, Color: 35 ppm <b>Scan</b> B/W: 80 ppm, Color: 80 ppm (1 pass, 2 sided scanning: B/W 80 ppm, Color 80 ppm) [Standard Document (A4 LEF/Letter LEF), 200 dpi, to Folder.]

\*1: The minimum custom size is 49x85 mm / 2.0 x 3.4".

\*2: Custom sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm.

\*3: 70 gsm paper.

\*4: The scanning speed varies depending on the documents.

### HIGH CAPACITY FEEDER B1 (OPTIONAL)

<b>Paper Size</b>	A4 LEF, Letter LEF, JIS B5 LEF
<b>Paper Weight</b>	55 to 216 gsm / 15 lb. bond to 57 lb. bond
<b>Feeding Capacity / Number of Tray*1</b>	2000 sheets x 1-tray
<b>Dimensions</b>	W 389 x D 610 x H 377 mm / W 15.4 x D 24.1 x H 14.9"
<b>Weight</b>	29 kg / 64 lb.
<b>Space Requirement*2</b>	W 1056 x D 720 mm / W 41.6 x D 28.4"

\*1: 80 gsm paper.

\*2: Main Unit + High Capacity Feeder B1 ; When the Bypass Tray are fully extended.

### Finisher-A2(Optional)

<b>Type</b>	Sort (Offset available) / Stack (Offset available) Default: No Offset
<b>Paper Size</b>	Max: A3, 11 x 17"; Min: Postcard (100 x 148 mm)
<b>Paper Weight</b>	60 to 256 gsm / 16 lb. bond to 142 lb. index
<b>Paper Capacity*1</b>	[Without Stapling] A4: 500 sheets; JIS B4: 250 sheets; A3 or larger: 200 sheets; Mixed Size Stacking*2: 250 sheets [With Stapling] 30 sets
<b>Staple</b>	Capacity 60 to 256 gsm / 16 lb. bond to 142 lb. index Paper Size Max: A3, 11 x 17"; Min: JIS B5 LEF Paper Weight 60 to 256 gsm / 16 lb. bond to 142 lb. index Position Single stapling, Dual stapling
<b>Dimensions</b>	W 658 x D 461 x H 238 mm / W 25.9 x D 18.2 x H 9.4" 11 kg / 25lb
<b>Space Requirement (When connected to the main unit) *2</b>	W 1132 x D 659 mm / W 44.6 x D 26.0"

\*1: 70 gsm paper.

\*2: When larger size sheets are stacked on top of smaller size sheets.

\*3: Width 478 mm when the paper support is stored.

\*4: Main Unit + Finisher-A2; when the paper support is pulled out and the Bypass Tray is fully extended.

## FINISHER-B4 (OPTIONAL)

<b>Type</b>	Sort (Offset available <sup>*1*</sup> ) / Stack (Offset available <sup>*1*</sup> )
<b>Paper Size<sup>*3</sup></b>	Max: A3, 11 x 17"; Min: A5
<b>Paper Weight<sup>*4</sup></b>	60 to 256 gsm / 16 lb. bond to 142 lb. index
<b>Paper Capacity<sup>*5</sup></b>	[Without Stapling] A4: 2000 sheets, JIS B4 or larger: 1000 sheets, Mixed Size Stacking <sup>*6</sup> : 300 sheets [With Stapling] A4: 100 sets or 1000 sheets <sup>*7</sup> , JIS B4 or larger: 75 sets or 750 sheets [With Booklet Finishing <sup>*8</sup> ] 50 sets or 600 sheets [With Fold <sup>*9</sup> ] 500 sheets
<b>Staple</b>	<b>Capacity</b> 50 sheets (90 gsm or less)
	<b>Paper Size<sup>*10</sup></b> Max: A3, 11 x 17"; Min: A5 LEF
	<b>Paper Weight</b> 60 to 256 gsm / 16 lb. bond to 142 lb. index
	<b>Position</b> Single stapling, Dual stapling
<b>Punch<sup>*11</sup></b>	<b>Number of Holes</b> 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications)
	<b>Paper Size<sup>*12</sup></b> Max: A3, 11 x 17"; Min: A5 LEF
	<b>Paper Weight</b> 60 to 220 gsm / 16 lb. bond to 122 lb. index
	<b>Capacity</b> Saddle Staple: 15 sheets; Single Fold: 5 sheets
<b>Booklet Finishing<sup>*8</sup></b>	<b>Paper Size</b> Max: A3, 11 x 17"; Min: A4, Letter
	<b>Paper Weight</b> Saddle Staple: 60 to 80 gsm / 16 lb. bond to 21 lb. bond <sup>*13</sup> Single Fold: 60 to 105 gsm / 18 lb. bond to 28 lb. bond
<b>Dimensions<sup>*14</sup></b>	W 607 x D 653 x H 1041 mm / W 23.9 x D 25.7 x H 41.0" With Booklet Finisher: W 607 x D 673 x H 1079 mm / W 23.9 x D 26.5 x H 42.5"
<b>Weight <sup>*15</sup></b>	26 kg / 58 lb. Punch Kit: + 2 kg / 5 lb. Booklet Maker Unit: + 10 kg / 22 lb.
<b>Space Requirement (When connected to the main unit) <sup>*16</sup></b>	W 1519 x D 659 mm / W 59.8 x D 26.0" With Booklet Finisher: W 1519 x D 673 mm / W 59.8 x D 26.5"

Installation Kit Required.

Note: Finisher-B4 is available only when optional 1 Tray Module or 3 Tray Module or Tandem Tray Module is attached to Main Unit.

\*1: The offset feature is set to disabled by factory default. The setting can be changed as necessary.

\*2: Outputs less than 210 mm width are delivered without offset stacking.

\*3: Paper in the sizes larger than A3 or 11 x 17" or smaller than A5 are delivered to the Centre Tray.

\*4: 70 gsm paper.

\*5: When larger size sheets are stacked on top of smaller size sheets.

\*6: 75 sets or 750 sheets with dual stapling.

\*7: The Booklet Finishing function requires the optional Booklet Maker Unit for Finisher-B. Make a crease allows you to fold easily. After a job with the Booklet Finishing function specified has been output, the next job may not be delivered until the sheets are removed from the output tray. Also, if larger size sheets are stacked on top of smaller size sheets after a job with the Booklet Finishing function specified has been run, the next job may not be delivered until the sheets are removed from the output tray.

\*8: Available staple positions vary depending on the paper size.

\*9: The Punch function requires the optional 2/4 Hole Punch Kit for Finisher-B or US 2/3 Hole Punch Kit for Finisher-B

\*10: Available number of punch holes varies depending on the paper size.

\*11: Covers can be up to 220 gsm (Extra Heavyweight).

\*12: Inner connector within the body is excluded.

\*13: Main Unit + Finisher-B4; When the paper support is pulled out and the Bypass Tray is fully extended.

## Arivia M2125, M2130, M3135

### MONOCHROME A3 MULTIFUNCTION PRINTER

Katun's portfolio of Arivia MFP's for large workgroups feature state-of-the-art technology that makes it easy to run your business and maximize productivity. Designed to integrate into any office environment, Arivia MFP's are designed to withstand today's security threats, offer an intuitive user experience, and deliver enhanced workflow solutions. Smartly designed for reliability and to minimize service calls, and with print speeds up to 65ppm, scan speeds up to 270ppm and a full range of input and finishing options, Arivia is powerful asset to your business.



For complete information on Katun products, please visit: [www.katun.com](http://www.katun.com)

© 2024 Katun. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

24-08-0003-KBS ©2024 Katun Corporation

# KATUN®

7760 France Ave. So. Suite 340  
Minneapolis, MN 55435  
1-800-328-2965 | [katun.com](http://katun.com)

